

MasterFlow

THE NAME YOU CAN TRUST

End Feed Fitting Specification



- Suitable for hot and cold drinking water, heating and chilled water systems.
- Ideal for confined spaces.
- Available in sizes 8 - 54 mm.
- Manufactured from high quality copper material in accordance with EN 124-2.
- Suitable for connecting copper tubes in accordance with EN 1057.
- Designed for solder and brazing applications*.

Applications & Technical Information

Drinking water	Y
Sanitary water	Y
Heating and chilled water systems	Y
Compressed air	Y
Gas	Y
Available sizes	8 - 54 mm
Operating parameters solder 6 - 54 mm	Using tin silver 95/5% 25 bar at 0°C to 30°C 25 bar at 65°C 19 bar at 95°C 16 bar at 110°C
	Using tin lead 50/50% or 60/40% 16 bar at 0°C to 30°C
Operating parameters brazed 15 mm	35.1 bar at -20°C to 110°C
	29.8 bar at 150°C
Material	Copper and yellow brass

*with the exception of Union fittings with copper tails which can only be soft soldered.

Tel: 0161 667 2331 | Fax: 0161 973 7025

diane.mason@masterflow.uk.com | www.masterflow.uk.com

MasterFlow Ltd. 70 - 76 Great Bridge Water Street, Manchester, Lancashire, M1 5ES, UK